## Information dynamics in a model of EEG brain rhythms

<u>Gustavo Menesse</u>\*

Department of Electromagnetism and Matter's Physics - Faculty of Science - University of Granada, Spain

Joaquín J. Torres $^{\dagger}$ 

Institute Carlos I for Theoretical and Computational Physics - University of Granada, Spain (Dated: June 29, 2023)

In recent years, several new information theory tools were developed to study complex systems. One of them is information dynamics (ID), which studies how a complex system locally stores, transfers, and modifies information. Another tool is Partial Information Decomposition (PID), which analyses the information between random variables by decomposing it into three types of information "atoms": unique, redundant, and synergistic, each of them capturing different fundamental relations between variables. A recently developed framework called Integrated Information decomposition  $(\Phi-ID)[4]$  is constructed using ideas from Integrated Information Theory (IIT) [3] and both ID and PID, providing a more general framework for exploring information dynamics in complex systems. In this study, we apply  $\Phi$ -ID to explore the behavior of a neuronal network with a rich and well-known phase diagram [5] with different emerging dynamical phases associated with familiar brain waves observed in EEG recordings. Our analysis shows that: i) the system has the maximum integrated information  $\Phi^R$  in a region where excitatory neurons exhibit the maximum variance, in a transition between intermediate neuronal activity with clear dominant rhythms  $\beta$  and high activity where  $\gamma$  oscillations dominates; ii) local information transfer appears to be maximum in a metastable region where  $\delta$  and  $\beta$  waves dominates; iii) at short time scales, the inhibitory population has maximum information storage close to a first-order transition. In conclusion, in our model, the emergence of EEG-like rhythms at the collective level encompasses a rich information dynamics. This simple model can help to better understand the relationship between different brain rhythms and local information dynamics.

Lizier, J. T. (2013). The Local Information Dynamics of Distributed Computation in Complex Systems. Springer Berlin Heidelberg.

<sup>[2]</sup> Barrett, A. B. (2015). Exploration of synergistic and redundant information sharing in static and dynamical Gaussian systems. Physical Review E - Statistical, Nonlinear, and Soft Matter Physics, 91(5).

<sup>[3]</sup> Tononi, G., Boly, M., Massimini, M., & Koch, C. (2016). Integrated information theory: From consciousness to its physical substrate. In Nature Reviews Neuroscience (Vol. 17, Issue 7, pp. 450–461). Nature Publishing Group.

<sup>\*</sup> mereles930@gmail.com

<sup>&</sup>lt;sup>†</sup> jtorres@onsager.ugr.es

- [4] Mediano, P. A. M., Rosas, F. E., Farah, J. C., Shanahan, M., Bor, D., & Barrett, A. B. (2022). Integrated information as a common signature of dynamical and information-processing complexity. Chaos, 32(1).
- [5] Pretel, J., Torres, J. J., Marro, J., Mirasso, C. R., & Valizadeh, A. (2021). EEGs Disclose Significant Brain Activity Correlated with Synaptic Fickleness.