

QUANTUM MACHINE LEARNING WITH QUDITS

Sebastián Roca-Jerat,* Juan Román-Roche, Fernando Luis, and David Zueco

Instituto de Nanociencia y Materiales de Aragón (CSIC - Universidad de Zaragoza)

(Dated: June 12, 2023)

Quantum machine learning (QML) is recently gaining interest in both theory and experiment thanks to variational circuits implemented in the noisy intermediate-scale quantum computers (NISQs) [1]. Since we are in such an era, algorithms capable of being implemented in small circuits are of great interest. In pursuit of this objective, we explore QML algorithms that are implementable in circuits involving a single qudit, a system with $d > 2$ levels, instead of the traditional qubit ($d = 2$). Molecules with large electronic and/or nuclear spins provide a natural platform with multiple operational levels [2], being a suitable choice for implementing our qudits. Operations are driven by electromagnetic pulses resonant with the allowed transitions, which can be realized with EPR techniques or by coupling them to superconducting circuits [3]. It has been shown that this type of control in a single qudit is sufficient to implement any d -dimensional unitary operation [4], thus being an universal quantum processing unit. Specifically, we explore supervised learning [5] and classification problems of databases comprising more classes than levels are accessible in our qudit, forcing the development of tools to find maximally orthogonal states [6].

-
- [1] J. Preskill *Quantum* **2**, 79 (2018).
 - [2] I. Gimeno et al. *Chem.* **12(15)**, 5621-5630 (2021).
 - [3] V. Rollano et al. *Commun. Phys.* **5(1)**, 1-9 (2022).
 - [4] A. Castro et al. *Phys. Rev. Appl.* **17(6)**, 064028 (2022).
 - [5] M. Schuld et al. *Phys. Rev. Lett.* **122**, 040504 (2019).
 - [6] A. Pérez-Salinas et al. *Quantum* **4**, 226 (2020).

* sroca@unizar.es